Full-scale numerical calculation of ballasted tracks with the Discrete Element Method



Joaquín Irazábal, Fernando Salazar and Eugenio Oñate

https://github.com/KratosMultiphysics/Kratos
http://gid.cimne.upc.es/









Ballast | Sleepers | Rails, bearing plates | Boundary walls | Subballast |
| Full scale railway track tests | Summary and ongoing work



Full-scale test



Good results applying the Hertz-Mindlin contact model



Simple compression – Hertz



Paderno C. Simulation of ballast behaviour under traffic and tamping process. PhD Thesis 2009.

Hertzian contact model: contact stiffness depends on the contact volumen but does not take into account edge breakage

Real contact geometry

Numerical contact geometry

Conical damage contact model: accounts for edge breakage

Two new material properties to define: Maximum stress and α



Initial radius



Final Radius and offset

Harkness, J., Zervos, A., Le Pen, L., Aingaran, S., & Powrie, W. (2016). Discrete element simulation of railway ballast: modelling cell pressure effects in triaxial tests. Granular Matter, 18(3), 65.

Simple compression – Conical damage



Paderno C. Simulation of ballast behaviour under traffic and tamping process. PhD Thesis 2009.

Sleepers



Full-scale test



Rigid bodies and simplified geometry

Sleepers contact parameters

Young modulus = 30 Gpa (prestressed concrete)

Friction coefficient = 0.7247*

* Zand, J. van't, & Moraal, J. (1997) Roads and Railways Research Laboratory Technical University of Delft









Full-scale test





Axial loading: $\sigma_x = \frac{P}{A}$

Torsion: $\tau = \frac{T\rho}{J}$



Bending: $\sigma_x = -\frac{My}{I}$





Large deformations
Non-linear problem
} Analytical solution unknown ⇨ FEM


P
y
x
P
y
x
P
y
x
P
y
x

E = 117.21 GPa, v = 0.35,
L = 0.204 m and R = 0.006 m

P = 450 N



P = 4500 N






A
Ixx
Iyy


kr
kn

Bearing plates



k_{bp} = 30 – 50 kN/mm



Pita, A. L., Teixeira, P. F., & Robusté, F. (2004). High speed and track deterioration: the role of vertical stiffness of the track. Proceedings of the Institution of Mechanical Engineers, Part F: Journal of Rail and Rapid Transit, 218(1), 31-40.









Full-scale test







Contact between ballast and boundary walls

Young modulus = 200 Mpa*

Friction coefficient = 0.0 (“mirrored particles”)

* Paderno, C. Simulation of ballast behaviour under traffic and tamping process. 9th Swiss Transport Research Conference. 2009.









Full-scale test



Ballast | Sleepers | Rails, bearing plates | Boundary walls | **Subballast** |
| Full scale railway track tests | Summary and ongoing work





k_{sub} = 70 – 110 kN/mm

Pita, A. L., Teixeira, P. F., & Robusté, F. (2004). High speed and track deterioration: the role of vertical stiffness of the track. Proceedings of the Institution of Mechanical Engineers, Part F: Journal of Rail and Rapid Transit, 218(1), 31-40.


Ballast


Sleepers


Rails and bearing plates


Full-scale test


Boundaries


Subballast

Full scale tests



- Scenario 1: Well compacted track
- Scenario 2: Poorly compacted track
- Scenario 3: Fouled track (less friction* and larger contact volume between particles)

*Huang, H. & Tutumluer, E. (2011). Discrete Element Modeling for fouledrailroad ballast. Construction and Building Materials, 25 (8) 3306–3312.

Full scale tests

$Q = 168732$ N	Axle load
$v = 250$ km/h	Velocity of the train
$R = 4000$ m	Radius of the curve
$A = 77.45$ cm^2	Rail cross section
$I_{xx} = 3217$ cm^4	Moment of inertia horizontal axis
$I_{yy} = 524$ cm^4	Moment of inertia vertical axis



Full scale tests – Ballast lateral velocity



Full scale tests – Sleepers displacement



Full scale tests – Sleepers displacement



Full scale tests – Sleepers displacement





Summary and ongoing work

- Spherical particles are useful for evaluating the macroscopic behaviour of the track (not valid, for example, to analyse the distribution of contacts)
- The DEM can accurately reproduce the behavior of rails and bearing plates making easy the coupling with railway ballast discrete particles
- The numerical tool presented allows the user to test different situations:
  - Ballast granulometry or properties
  - Sleepers design
  - Bearing plates and rails

RESILTRACK (Resilience of Railway Infrastructures Against Climate Change)

- Analysing how to measure track deflections in a real railway track section (high-speed if possible)
- Searching more data to validate conical damage parameters and ballast fouling conditions
- Testing other particle geometries (clusters of spheres) more similar to ballast particles

Thank you for your attention!

Questions?

jirazabal@cimne.upc.edu